



Weight Chart

Snap-N-Lock Structural Insulated Panels

Thickness	.019 Aluminum lbs/sq.ft.	.024 Aluminum lbs/sq.ft.	.030 Aluminum lbs/sq.ft.	26 Gauge Steel lbs/sq.ft.
1"	.6334	.7994	1.0300	1.9774
2"	.7167	.8827	1.1133	2.0607
3"	.8000	.9660	1.1966	2.1440
4"	.8833	1.0493	1.2799	2.2273
5"	.9666	1.1326	1.3632	2.3106
6"	1.0499	1.2159	1.4465	2.3939
8"	1.1332	1.2992	1.5298	2.4772

Floor Panels

7/16" OSB / Foam / 7-16" OSB

Thickness	Lbs/Sq.Ft.
4-1/2"	3.3125
6-1/2"	3.4791
8-1/2"	3.6457

Floor Panel w/ Metal Vapor Barrier

7/16" OSB / Foam / 7-16" OSB / .024 Aluminum

Thickness	Lbs/Sq.Ft.
4-1/2"	3.6559
6-1/2"	3.8225
8-1/2"	3.9891

Half-Snap Structural Insulated Panels

Thickness	.024 Aluminum lbs/sq.ft.	.030 Aluminum lbs/sq.ft.
4"	2.2392	2.3557
6"	2.4058	2.5223
8"	2.5724	2.6889

Half-Snap w/ Metal Vapor Barrier

Thickness	.024 Aluminum lbs/sq.ft.	.030 Aluminum lbs/sq.ft.
4"	2.5826	2.8136
6"	2.7492	2.9802
8"	2.9158	3.1868

5-Ply Spandrel Panels

.024 Aluminum / 1/8" Hard Board / Foam /
1/8" Hard Board / .024 Aluminum

Thickness	Lbs/Sq.Ft.
1"	1.9940
2"	2.0827
3"	2.1660
4"	2.2493

Material Weights

Material	Lbs/Sq.Ft.
.024 Aluminum	.3434
.030 Aluminum	.4579
.0217 Steel	.9314
7/16" OSB	1.5000
1/8" Hard Board or Forestex	.5625